

auxiliary contact SDE - 6 A - 1 NO/ NC - for Masterpact NT

47078

EAN Code: 3303430470786

Main

Device Short Name	SDE
Product Or Component Type	Auxiliary contact
Device Application	Connection
Range Compatibility	Masterpact MasterPact NT circuit breaker
Signal Contacts Composition	1 NO/NC

Complementary

Auxiliary Contacts Type	Standard
[Ith] Conventional Free Air Thermal Current	6 A
[le] Rated Operational Current	AC-12: 3 A at 690 V AC 50/60 Hz
	DC-12: 3 A at 24/48 V DC
	AC-12: 5 A at 240/380 V AC 50/60 Hz
	AC-12: 5 A at 480 V AC 50/60 Hz
	DC-12: 0.15 A at 250 V DC
	DC-12: 0.3 A at 125 V DC
Minimum Load	100 mA at 24 V
Accessory / Separate Part	Spare parts for MasterPact NT

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.0 cm
Package 1 Width	5.0 cm
Package 1 Length	21.0 cm
Package 1 Weight	22.0 g
Unit Type Of Package 2	S03
Number Of Units In Package 2	100
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	2.587 kg

Contractual warranty

Warranty 18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Well-being performance

Toxic Heavy Metal Free	
Mercury Free	
Rohs Exemption Information	Yes
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins