



Main

| | |
|-------------------------------------|---|
| Range | Acti 9 |
| Product name | Acti 9 iDPN N Vigi |
| Product or component type | Residual current breaker with overcurrent protection (RCBO) |
| Device short name | IDPN N Vigi |
| Device application | Distribution |
| Poles description | 1P + N |
| Number of protected poles | 1 |
| Neutral position | Left |
| [In] rated current | 32 A |
| Network type | AC |
| Trip unit technology | Thermal-magnetic |
| Curve code | C |
| Earth-leakage sensitivity | 30 mA |
| Earth-leakage protection time delay | Instantaneous |
| Earth-leakage protection class | Type AC |
| Breaking capacity | 6000 A Icn at 220...240 V AC 50 Hz conforming to EN/IEC 61009-2-1 |
| Suitability for isolation | Yes conforming to EN/IEC 60947-2 |

Complementary

| | |
|---------------------------------------|---|
| Device location in system | Outgoer |
| Network frequency | 50 Hz |
| [Ue] rated operational voltage | 220...240 V AC 50 Hz |
| Magnetic tripping limit | 5...10 x In |
| Residual current tripping technology | Voltage independent |
| [Ics] rated service breaking capacity | 6000 A 100 % x Icn at 220...240 V AC 50 Hz conforming to EN/IEC 61009-2-1 |
| Rated breaking and making capacity | I _{dm} 6000 A at 220...240 V AC 50 Hz conforming to EN/IEC 61009-2-1 |
| Limitation class | 3 conforming to EN/IEC 61009-2-1 |

| | |
|--|--|
| [Ui] rated insulation voltage | 400 V AC 50 Hz |
| [Uimp] rated impulse withstand voltage | 4 kV |
| Contact position indicator | Yes |
| Control type | Toggle |
| Local signalling | ON, OFF, fault trip |
| Mounting mode | Clip-on |
| Mounting support | DIN rail |
| 9 mm pitches | 4 |
| Height | 85 mm |
| Width | 36 mm |
| Depth | 73 mm |
| Net weight | 125 g |
| Colour | White |
| Mechanical durability | 20000 cycles |
| Electrical durability | 10000 cycles |
| Locking options description | Padlocking device |
| Connections - terminals | Single terminal top or bottom1...16 mm ² rigid Single terminal top or bottom1...10 mm ² flexible Single terminal top or bottom1...10 mm ² flexible with ferrule |
| Wire stripping length | 15 mm for top or bottom connection |
| Tightening torque | 2 N.m top or bottom |
| Earth-leakage protection | Integrated |

Environment

| | |
|---------------------------------------|--|
| Standards | EN/IEC 61009-2-1 |
| Product certifications | VDE GOST |
| IP degree of protection | IP20 conforming to IEC 60529 IP40 (modular enclosure) conforming to IEC 60529 |
| Pollution degree | 3 |
| Overvoltage category | III conforming to IEC 60364 |
| Electromagnetic compatibility | 8/20 µs impulse withstand, 250 A conforming to EN/IEC 61009-2-1 |
| Tropicalisation | 2 conforming to IEC 60068-1 |
| Relative humidity | 95 % at 55 °C |
| Ambient air temperature for operation | -5...60 °C |
| Ambient air temperature for storage | -40...85 °C |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

A9D31632 is replaced by:



**Residual Current Breaker with Overcurrent protection (RCBO)
A9DE3632**

residual current breaker with overcurrent protection (RCBO), Acti9 iCV40, 1P+N, 32 A,
C Curve, 6000 A, 30 mA, AC type

Qty 1

Reason for Substitution: End of life | Substitution date: 31 December 2020
