

Price* : 481.19 GBP



Main

Range of product	Harmony XK
Product or component type	Complete joystick controller
Product specific application	Light hoisting applications

Complementary

Device short name	XKB
Bezel material	Metal
Fixing collar material	Metal
Sale per indivisible quantity	1
Protective treatment	TC
Ambient air temperature for storage	-40...70 °C
Ambient air temperature for operation	-20...70 °C
Overvoltage category	Class I conforming to IEC 61140
Standards	UL 508 EN/IEC 60947-5-1 CSA C22.2 No 14
Operator position information	All positions
Operator profile	Handle with zero position mechanical interlock
Notch per direction	1...3 notches at 0-12°-20°-28° for each direction
Mechanical durability	1000000 cycles
Vibration resistance	6 gn (f= 1...70 Hz) conforming to IEC 60068-2-6
Shock resistance	20 gn (duration = 11 ms) conforming to IEC 60068-2-27
Connections - terminals	Captive screw clamp terminals, <= 2 x 1.5 mm ² with cable end Captive screw clamp terminals, <= 1 x 2.5 mm ² without cable end Captive screw clamp terminals, >= 1 x 0.5 mm ²
Short-circuit protection	10 A cartridge fuse type gG conforming to EN/IEC 60947-5-1
[I _{th}] conventional free air thermal current	10 A conforming to EN/IEC 60947-5-1 10 A conforming to CSA C22.2 No 14 10 A conforming to UL 508
[U _i] rated insulation voltage	500 V (pollution degree 3) conforming to IEC 60947-1
Compatibility code	XKB

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Contractual warranty

Warranty	18 months
----------	-----------
